

Foam (AFFF) stored pressure fire extinguishers

Wheeled



- Steel cylinders welded with MIG system (Metal Inert Gas).
- 100% Hydrostatically tested.
- Unique surface treatment, highly resistant to corrosion: mechanical pickled, phosphatized, passivated and painted with polyester powder paint.
- Forged brass valve with pressure gauge.
- Synthetic rubber hose of great maneuverability.
- Ventouri type nozzle with handle and trigger.
- Great maneuverability equipment. The wheel design allows to easy move the device.
- Compressed air pressurization.
- Easy to use equipment. Simple maintenance.
- Non-toxic biodegradable agent. Excellent sealing of vapors and heat resistance thus giving a high burn back tolerance. Low surface tension.

| Tech Specs | | | | | | | |
|--------------------------------|--------------------|--------------------|-------------------------|--------------------|-------------------------|---------------------|--------------------------|
| | 25 dm ³ | 50 dm ³ | 50 dm ³ Ø800 | 70 dm ³ | 70 dm ³ Ø800 | 100 dm ³ | 100 dm ³ Ø800 |
| Nominal capacity (kg) | 25 | 50 | 50 | 70 | 70 | 100 | 100 |
| Loaded weight (kg) | 55 | 100 | 136 | 140 | 177 | 185 | 216 |
| Height (mm) | 1.140 | 1.210 | 1.300 | 1.350 | 1.405 | 1.400 | 1.515 |
| Width (mm) | 455 | 466 | 685 | 575 | 750 | 630 | 750 |
| Depth (mm) | 600 | 670 | 805 | 736 | 835 | 840 | 920 |
| Wheel diameter (mm) | 300 | 350 | 800 | 350 | 800 | 400 | 800 |
| Hose length (m) | 5 | 5 | 5 | 5 | 5 | 12 | 12 |
| Discharge time (s) | 120 | 130 | 130 | 150 | 150 | 170 | 170 |
| Discharge range (m) | 5/6 | 6/7 | 6/7 | 7/8 | 7/8 | 8/9 | 8/9 |
| Temperature range (°C) | -10 to 50 | -10 to 50 | -10 to 50 | -10 to 50 | -10 to 50 | -10 to 50 | -10 to 50 |
| Service pressure (Mpa) | 0,8 | 0,8 | 0,8 | 0,8 | 0,8 | 0,8 | 0,8 |
| Tested pressure (Mpa) | 4,0 | 4,0 | 4,0 | 4,0 | 4,0 | 4,0 | 4,0 |
| Extinguishing agent IRAM std.# | 3515 | 3515 | 3515 | 3515 | 3515 | 3515 | 3515 |
| Fire extinguisher IRAM std.# | 3541 | 3541 | 3541 | 3541 | 3541 | 3541 | 3541 |

| Models | | | | | | | |
|--------|------|------|------|------|------|------|------|
| Code | B203 | B207 | B327 | B211 | B328 | B215 | B228 |

AFFF extinguishing agent is certified under UL 162 standards