

BC Dry Chemical Powder stored pressure fire extinguishers

Wheeled



- Steel cylinders welded with MIG system (Metal Inert Gas).
- 100% Hydrostatically tested.
- Unique surface treatment, highly resistant to corrosion: mechanical pickled, phosphatized, passivated and painted with polyester powder paint.
- Forged brass valve with pressure gauge.
- Synthetic rubber hose of great maneuverability.
- Nozzle with handle and trigger.
- Great maneuverability equipment. The wheel design allows to easy move the device.
- Nitrogen gas pressurization.
- Easy to use equipment. Simple maintenance.

Tech Specs							
	25 kg	50 kg	50 kg Ø800	70 kg	70 kg Ø800	100 kg	100 kg Ø800
Nominal capacity (kg)	25	50	50	70	70	100	100
Loaded weight (kg)	55	100	136	140	177	185	216
Height (mm)	1.140	1.210	1.300	1.350	1.405	1.400	1.515
Width (mm)	455	466	685	575	750	630	750
Depth (mm)	600	670	805	736	835	840	920
Wheel diameter (mm)	300	350	800	350	800	400	800
Hose length (m)	5	5	5	5	5	12	12
Discharge time (s)	40	45	45	50	50	55	55
Discharge range (m)	5/6	6/7	6/7	7/8	7/8	8/9	8/9
Temperature range (°C)	-20 to 50	-20 to 50	-20 to 50	-20 to 50	-20 to 50	-20 to 50	-20 to 50
Service pressure (Mpa)	1,4	1,4	1,4	1,4	1,4	1,4	1,4
Tested pressure (Mpa)	4,0	4,0	4,0	4,0	4,0	4,0	4,0
Extinguishing agent IRAM std.#	3569	3569	3569	3569	3569	3569	3569
Fire extinguisher IRAM std.#	3550	3550	3550	3550	3550	3550	3550
Models							
BC Sódico	B217	B218	B331	B219	B220	B243	B333
BC Purple K	B229	B230	B247	B231	B324	B245	B237
BC Monex	B225	B222	B325	B223	B326	B244	B238