

Carbon dioxide stored pressure fire extinguishers

Portable and wheeled



- Steel cylinder without sew
- 100% Hydrostatically tested.
- Surface treatment. Painted with vitric painting.
- Forged brass valve with different auctioning systems (robinet, trigger and lever). Safety device.
- Synthetic dielectric rubber hose with steel mesh. Dielectric nozzle.

Tech Specs											
Nominal capacity (kg)	1kg	2kg	3,5kg	5kg	7kg	10kg	20kg	20kg ^(*)	30kg	40kg ^(*)	60kg ^(*)
Loaded weight (kg)	4	9	14	20	29	35	61	70	100	122	200
Height (mm)	340	520	600	790	1000	1215	940	1330	1315	1060	1435
Width (mm)	89	254	250	310	335	335	472	442	472	710	710
Depth (mm)	89	114	140	140	270	270	410	320	410	490	490
Wheel diameter (mm)	-	-	-	-	-	200	380	300	380	500	500
Hose length (m)	-	-	-	900	900	1800	3000	3000	3000	3000	3000
Discharge time (s)	14	9	9	14	30	50	70	70	120	120	150
Discharge range (m)	1,5/3										
Temperature range (°C)	-20 to 50										
Service pressure (Mpa)	15	15	15	15	15	15	15	15	15	15	15
Tested pressure (Mpa)	25	25	25	25	25	25	25	25	25	25	25
Extinguishing agent IRAM std.#	41170										
Fire extinguisher IRAM std.#	3509	3509	3509	3509	3509	3565	3565	3565	3565	3565	3565
Wall bracket	Yes	Yes	Yes	Yes	Yes	No	No	No	No	No	No
Models											
Code	C301	C302	C303	C304	C305	C306	C307	C308	C309	C310	C311
Extinguishing rating	-	2B-C	3B-C	5B-C	5B-C	-	-	-	-	-	-