

Wet chemical (AK) stored pressure fire extinguishers

Portable



- Stainless steel cylinders welded with TIG system (Tungsten Inert Gas). Not magnetic.
- 100% Hydrostatically tested.
- Unique surface treatment. Semi matt polished extinguisher.
- Forged brass valve with pressure gauge.
- Synthetic dielectric rubber hose of great maneuverability.
- The nozzle produces a very thin spray that increases the cooling power and doesn't allow the grease to spread.
- Compressed air pressurization.
- Easy to use compact equipment. Simple maintenance.
- The wet agent is an aqueous solution of potassium acetate, specially designed to be used in commercial kitchens with greases and oils of vegetal and animal origin.

Tech Specs		
Nominal capacity (kg)	6 dm³	10 dm³
Loaded weight (kg)	8,25	13,00
Height (mm)	470	620
Width (mm)	270	270
Depth (mm)	190	190
Discharge time (s)	50	75
Discharge range (m)	3/4	3/4
Temperature range (°C)	5 to 50	5 to 50
Service pressure (Mpa)	0,8	0,8
Tested pressure (Mpa)	2,0	2,0
Extinguishing agent IRAM std.#	3697	3697
Fire extinguisher IRAM std.#	3694	3694
Wall bracket	Yes	Yes
Models		
Code	A148	A149