

ABC Dry Chemical Powder stored pressure fire extinguishers

Portable



- Steel cylinders welded with MIG system (Metal Inert Gas).
- 100% Hydrostatically tested.
- Unique surface treatment, highly resistant to corrosion: mechanical pickled, phosphatized, passivated and painted with polyester powder paint.
- Forged brass valve with pressure gauge.
- Synthetic rubber hose of great maneuverability.
- Nitrogen gas pressurization.
- Easy to use compact equipment. Simple maintenance.

Tech Specs					
	1 kg Ø3	1 kg Ø4	2,5 kg	5 kg	10 kg
Nominal capacity (kg)	1,90	1,70	4,60	8,50	16,50
Loaded weight (kg)	340	250	415	480	655
Height (mm)	92	110	220	225	230
Width (mm)	76	101	125	153	182
Discharge time (s)	8/9	8/9	9/12	10/13	18/22
Discharge range (m)	2/3	2/3	3/4	5/6	6/7
Temperature range (°C)	-20 to 50	-20 to 50	-20 to 50	-20 to 50	-20 to 50
Service pressure (Mpa)	1,4	1,4	1,4	1,4	1,4
Tested pressure (Mpa)	3,5	3,5	3,5	3,5	3,5
Extinguishing agent IRAM std.#	3569	3569	3569	3569	3569
Fire extinguisher IRAM std.#	3523	3523	3523	3523	3523
Strap bracket	Yes	Yes	Optional	Optional	Optional
Wall bracket	No	No	Yes	Yes	Yes

Models					
ABC 60	A122	A131	A101	A102	A103
Extinguishing rating ABC 60	1A-3B-C	1A-3B-C	3A-20B-C	6A-40B-C	6A-60B-C
ABC 90	A114	A115	A151	A152	A153
Extinguishing rating ABC 90	Consult	Consult	3A-20B-C	10A-40B-C	10A-60B-C