

Water stored pressure fire extinguishers

Wheeled



- Steel cylinders welded with MIG system (Metal Inert Gas).
- 100% Hydrostatically tested.
- Unique surface treatment, highly resistant to corrosion: mechanical pickled, phosphatized, passivated and painted with polyester powder paint.
- Forged brass valve with pressure gauge.
- Synthetic rubber hose of great maneuverability.
- Nozzle with handle and trigger.
- Great maneuverability equipment. The wheel design allows to easy move the device.
- Compressed air pressurization.
- Easy to use equipment. Simple maintenance.

Tech Specs							
	25 dm ³	50 dm ³	50 dm ³ Ø800	70 dm ³	70 dm ³ Ø800	100 dm ³	100 dm ³ Ø800
Nominal capacity (kg)	25	50	50	70	70	100	100
Loaded weight (kg)	55	100	136	140	177	185	216
Height (mm)	1.140	1.210	1.300	1.350	1.405	1.400	1.515
Width (mm)	455	466	685	575	750	630	750
Depth (mm)	600	670	805	736	835	840	920
Wheel diameter (mm)	300	350	800	350	800	400	800
Hose length (m)	5	5	5	5	5	12	12
Discharge time (s)	105	120	120	130	130	130	130
Discharge range (m)	5/6	6/7	6/7	7/8	7/8	8/9	8/9
Temperature range (°C)	5 to 50	5 to 50	5 to 50	5 to 50	5 to 50	5 to 50	5 to 50
Service pressure (Mpa)	0,8	0,8	0,8	0,8	0,8	0,8	0,8
Tested pressure (Mpa)	4,0	4,0	4,0	4,0	4,0	4,0	4,0
Fire extinguisher IRAM std.#	3537	3537	3537	3537	3537	3537	3550
Models							
Code	B201	B205	B329	B209	B330	B240	B226