

## BC Dry Chemical Powder stored pressure fire extinguishers

Portable



- Steel cylinders welded with MIG system (Metal Inert Gas).
- 100% Hydrostatically tested.
- Unique surface treatment, highly resistant to corrosion: mechanical pickled, phosphatized, passivated and painted with polyester powder paint.
- Forged brass valve with pressure gauge.
- Synthetic rubber hose of great maneuverability.
- Nitrogen gas pressurization.
- Easy to use compact equipment. Simple maintenance.

Tech Specs			
Nominal capacity (kg)	<b>2,5 kg</b>	<b>5 kg</b>	<b>10 kg</b>
Loaded weight (kg)	4,60	8,50	16,50
Height (mm)	415	480	655
Width (mm)	220	225	230
Depth (mm)	125	153	182
Discharge time (s)	9/12	10/13	18/22
Discharge range (m)	3/4	5/6	6/7
Temperature range (°C)	-20 to 50	-20 to 50	-20 to 50
Service pressure (Mpa)	1,4	1,4	1,4
Tested pressure (Mpa)	3,5	3,5	3,5
Extinguishing agent IRAM std.#	3569	3569	3569
Fire extinguisher IRAM std.#	3523	3523	3523
Wall bracket	Yes	Yes	Yes
Strap bracket	Optional	Optional	Optional
Models			
BC Sódico	A110	A111	A112
BC Purple K	A135	A136	A137
Extinguishing rating BC Purple K	20B	40B	Consult
BC Monex	A128	A129	A130