



Company profile

Fadesa is the leader fire extinguisher brand in the Argentinean market. Based on a strong quality commitment, our vision is to protect the members of the society, its assets, the economic activity and the environment from the risks of a potential fire.

To achieve it, we insert ourselves in the development of the economic and productive systems of our country, participating actively in the fire protection industry, granting safety to our customers and to the final users of our products, thus positioning Fadesa as a synonym of reliability.



Much more than a fire extinguisher



Cautio S.R.L.

Index

ABC Dry Chemical Powder stored
pressure fire extinguishers

Portable 4

Wheeled 5

BC Dry Chemical Powder stored
pressure fire extinguishers

Portable 6

Wheeled 7

Water stored pressure fire
extinguishers

Portable 8

Wheeled 9

Foam (AFFF) stored pressure
fire extinguishers

Portable 10

Wheeled 11

Water mist stored pressure
fire extinguishers

12

HCFC stored pressure fire
extinguishers

13

HFC236fa stored pressure
fire extinguishers

14

Wet chemical (AK) stored
pressure fire extinguishers

15

Carbon dioxide stored pressure
fire extinguishers

16

D Dry Chemical Powder stored
pressure fire extinguishers

17

Automatic fire extinguishers

18

ABC Dry Chemical Powder stored pressure fire extinguishers

Portable

- Steel cylinders welded with MIG system (Metal Inert Gas).
- 100% Hydrostatically tested.
- Unique surface treatment, highly resistant to corrosion: mechanical pickled, phosphatized, passivated and painted with polyester powder paint.
- Forged brass valve with pressure gauge.
- Synthetic rubber hose of great maneuverability.
- Nitrogen gas pressurization.
- Easy to use compact equipment. Simple maintenance.



Tech Specs					
Nominal capacity (kg)	1 kg Ø3	1 kg Ø4	2,5 kg	5 kg	10 kg
Loaded weight (kg)	1,90	1,70	4,60	8,50	16,50
Height (mm)	340	250	415	480	655
Width (mm)	92	110	220	225	230
Depth (mm)	76	101	125	153	182
Discharge time (s)	8/9	8/9	9/12	10/13	18/22
Discharge range (m)	2/3	2/3	3/4	5/6	6/7
Temperature range (°C)	-20 to 50	-20 to 50	-20 to 50	-20 to 50	-20 to 50
Service pressure (Mpa)	1,4	1,4	1,4	1,4	1,4
Tested pressure (Mpa)	3,5	3,5	3,5	3,5	3,5
Extinguishing agent IRAM std.#	3569	3569	3569	3569	3569
Fire extinguisher IRAM std.#	3523	3523	3523	3523	3523
Strap bracket	Yes	Yes	Optional	Optional	Optional
Wall bracket	No	No	Yes	Yes	Yes
Models					
ABC 60	A122	A131	A101	A102	A103
Extinguishing rating ABC 60	1A-3B-C	1A-3B-C	3A-20B-C	6A-40B-C	6A-60B-C
ABC 90	A114	A115	A151	A152	A153
Extinguishing rating ABC 90	Consult	Consult	3A-20B-C	10A-40B-C	10A-60B-C

We also provide with extinguishing agent ABC55 certified under UL711

ABC Dry Chemical Powder stored pressure fire extinguishers

Wheeled

- Steel cylinders welded with MIG system (Metal Inert Gas).
- 100% Hydrostatically tested.
- Unique surface treatment, highly resistant to corrosion: mechanical pickled, phosphatized, passivated and painted with polyester powder paint.
- Forged brass valve with pressure gauge.
- Synthetic rubber hose of great maneuverability.
- Nozzle with handle and trigger.
- Great maneuverability equipment. The wheel design allows to easy move the device.
- Nitrogen gas pressurization.
- Easy to use equipment. Simple maintenance.



Tech Specs							
Nominal capacity (kg)	25 kg	50 kg	50 kg Ø800	70 kg	70 kg Ø800	100 kg	100 kg Ø800
Loaded weight (kg)	55	100	136	140	177	185	216
Height (mm)	1.140	1.210	1.300	1.350	1.405	1.400	1.515
Width (mm)	455	466	685	575	750	630	750
Depth (mm)	600	670	805	736	835	840	920
Wheel diameter (mm)	300	350	800	350	800	400	800
Hose length (m)	5	5	5	5	5	12	12
Discharge time (s)	40	45	45	50	50	55	55
Discharge range (m)	5/6	6/7	6/7	7/8	7/8	8/9	8/9
Temperature range (°C)	-20 to 50	-20 to 50	-20 to 50	-20 to 50	-20 to 50	-20 to 50	-20 to 50
Service pressure (Mpa)	1,4	1,4	1,4	1,4	1,4	1,4	1,4
Tested pressure (Mpa)	4,0	4,0	4,0	4,0	4,0	4,0	4,0
Extinguishing agent IRAM std.#	3569	3569	3569	3569	3569	3569	3569
Fire extinguisher IRAM std.#	3550	3550	3550	3550	3550	3550	3550
Models							
ABC 60	B202	B206	B248	B210	B220	B214	B227
ABC 90	B235	B236	B321	B233	B322	B239	323

We also provide with extinguishing agent ABC55 certified under UL711

BC Dry Chemical Powder stored pressure fire extinguishers

Portable

- Steel cylinders welded with MIG system (Metal Inert Gas).
- 100% Hydrostatically tested.
- Unique surface treatment, highly resistant to corrosion: mechanical pickled, phosphatized, passivated and painted with polyester powder paint.
- Forged brass valve with pressure gauge.
- Synthetic rubber hose of great maneuverability.
- Nitrogen gas pressurization.
- Easy to use compact equipment. Simple maintenance.



	Tech Specs		
Nominal capacity (kg)	2,5 kg	5 kg	10 kg
Loaded weight (kg)	4,60	8,50	16,50
Height (mm)	415	480	655
Width (mm)	220	225	230
Depth (mm)	125	153	182
Discharge time (s)	9/12	10/13	18/22
Discharge range (m)	3/4	5/6	6/7
Temperature range (°C)	-20 to 50	-20 to 50	-20 to 50
Service pressure (Mpa)	1,4	1,4	1,4
Tested pressure (Mpa)	3,5	3,5	3,5
Extinguishing agent IRAM std.#	3569	3569	3569
Fire extinguisher IRAM std.#	3523	3523	3523
Wall bracket	Yes	Yes	Yes
Strap bracket	Optional	Optional	Optional
	Models		
BC Sódico	A110	A111	A112
BC Purple K	A135	A136	A137
Extinguishing rating BC Purple K	20B	40B	Consult
BC Monex	A128	A129	A130

BC Dry Chemical Powder stored pressure fire extinguishers

Wheeled

- Steel cylinders welded with MIG system (Metal Inert Gas).
- 100% Hydrostatically tested.
- Unique surface treatment, highly resistant to corrosion: mechanical pickled, phosphatized, passivated and painted with polyester powder paint.
- Forged brass valve with pressure gauge.
- Synthetic rubber hose of great maneuverability.
- Nozzle with handle and trigger.
- Great maneuverability equipment. The wheel design allows to easy move the device.
- Nitrogen gas pressurization.
- Easy to use equipment. Simple maintenance.



Buenos Aires
Gobierno de la Ciudad

Tech Specs							
Nominal capacity (kg)	25 kg	50 kg	50 kg Ø800	70 kg	70 kg Ø800	100 kg	100 kg Ø800
Loaded weight (kg)	55	100	136	140	177	185	216
Height (mm)	1.140	1.210	1.300	1.350	1.405	1.400	1.515
Width (mm)	455	466	685	575	750	630	750
Depth (mm)	600	670	805	736	835	840	920
Wheel diameter (mm)	300	350	800	350	800	400	800
Hose length (m)	5	5	5	5	5	12	12
Discharge time (s)	40	45	45	50	50	55	55
Discharge range (m)	5/6	6/7	6/7	7/8	7/8	8/9	8/9
Temperature range (°C)	-20 to 50	-20 to 50	-20 to 50	-20 to 50	-20 to 50	-20 to 50	-20 to 50
Service pressure (Mpa)	1,4	1,4	1,4	1,4	1,4	1,4	1,4
Tested pressure (Mpa)	4,0	4,0	4,0	4,0	4,0	4,0	4,0
Extinguishing agent IRAM std.#	3569	3569	3569	3569	3569	3569	3569
Fire extinguisher IRAM std.#	3550	3550	3550	3550	3550	3550	3550
Models							
BC Sódico	B217	B218	B331	B219	B220	B243	B333
BC Purple K	B229	B230	B247	B231	B324	B245	B237
BC Monex	B225	B222	B325	B223	B326	B244	B238

Water stored pressure fire extinguishers

Portable

- Stainless steel cylinders welded with TIG system (Tungsten Inert Gas).
- 100% Hydrostatically tested.
- Unique surface treatment. Semi matt polished extinguisher.
- Forged brass valve with pressure gauge.
- Synthetic rubber hose of great maneuverability.
- Compressed air pressurization.
- Easy to use compact equipment. Simple maintenance.



Tech Specs		
Nominal capacity (kg)		10 dm ³
Loaded weight (kg)		12,55
Height (mm)		620/650
Width (mm)		240
Depth (mm)		190
Discharge time (s)		55
Discharge range (m)		9/11
Temperature range (°C)		5 to 50
Service pressure (Mpa)		0,8
Tested pressure (Mpa)		2,0
Fire extinguisher IRAM std.#		3525
Wall bracket		Yes
Model		
Code		A161 Inox
Extinguishing rating		1A

Water stored pressure fire extinguishers

Wheeled

- Steel cylinders welded with MIG system (Metal Inert Gas).
- 100% Hydrostatically tested.
- Unique surface treatment, highly resistant to corrosion: mechanical pickled, phosphatized, passivated and painted with polyester powder paint.
- Forged brass valve with pressure gauge.
- Synthetic rubber hose of great maneuverability.
- Nozzle with handle and trigger.
- Great maneuverability equipment. The wheel design allows to easy move the device.
- Compressed air pressurization.
- Easy to use equipment. Simple maintenance.



Tech Specs							
Nominal capacity (kg)	25 dm ³	50 dm ³	50 dm ³ Ø800	70 dm ³	70 dm ³ Ø800	100 dm ³	100 dm ³ Ø800
Loaded weight (kg)	55	100	136	140	177	185	216
Height (mm)	1.140	1.210	1.300	1.350	1.405	1.400	1.515
Width (mm)	455	466	685	575	750	630	750
Depth (mm)	600	670	805	736	835	840	920
Wheel diameter (mm)	300	350	800	350	800	400	800
Hose length (m)	5	5	5	5	5	12	12
Discharge time (s)	105	120	120	130	130	130	130
Discharge range (m)	5/6	6/7	6/7	7/8	7/8	8/9	8/9
Temperature range (°C)	5 to 50	5 to 50	5 to 50	5 to 50	5 to 50	5 to 50	5 to 50
Service pressure (Mpa)	0,8	0,8	0,8	0,8	0,8	0,8	0,8
Tested pressure (Mpa)	4,0	4,0	4,0	4,0	4,0	4,0	4,0
Fire extinguisher IRAM std.#	3537	3537	3537	3537	3537	3537	3550
Models							
Code	B201	B205	B329	B209	B330	B240	B226

Foam (AFFF) stored pressure fire extinguishers

Portable

- Stainless steel cylinders welded with TIG system (Tungsten Inert Gas).
- 100% Hydrostatically tested.
- Unique surface treatment. Semi matt polished extinguisher.
- Forged brass valve with pressure gauge.
- Synthetic rubber hose of great maneuverability.
- Ventouri type nozzle.
- Compressed air pressurization.
- Easy to use compact equipment. Simple maintenance.
- Non-toxic biodegradable agent. Excellent sealing of vapors and heat resistance thus giving a high burn back tolerance. Low surface tension.



Tech Specs		
Nominal capacity (kg)		10 dm ³
Loaded weight (kg)		12,60
Height (mm)		620/650
Width (mm)		240
Depth (mm)		190
Discharge time (s)		55
Discharge range (m)		5/6
Temperature range (°C)		-10 to 50
Service pressure (Mpa)		0,8
Tested pressure (Mpa)		2,0
Extinguishing agent IRAM std.#		3515
Fire extinguisher IRAM std.#		3527
Wall bracket		Yes
Model		
Code		A162 Inox
Extinguishing rating		3A-10B

AFFF extinguishing agent is certified under UL 162 standards

Foam (AFFF) stored pressure fire extinguishers

Wheeled

- Steel cylinders welded with MIG system (Metal Inert Gas).
- 100% Hydrostatically tested.
- Unique surface treatment, highly resistant to corrosion: mechanical pickled, phosphatized, passivated and painted with polyester powder paint.
- Forged brass valve with pressure gauge.
- Synthetic rubber hose of great maneuverability.
- Ventouri type nozzle with handle and trigger.
- Great maneuverability equipment. The wheel design allows to easy move the device.
- Compressed air pressurization.
- Easy to use equipment. Simple maintenance.
- Non-toxic biodegradable agent. Excellent sealing of vapors and heat resistance thus giving a high burn back tolerance. Low surface tension.



Buenos Aires
Gobierno de la Ciudad

Tech Specs							
Nominal capacity (kg)	25 dm ³	50 dm ³	50 dm ³ Ø800	70 dm ³	70 dm ³ Ø800	100 dm ³	100 dm ³ Ø800
Loaded weight (kg)	55	100	136	140	177	185	216
Height (mm)	1.140	1.210	1.300	1.350	1.405	1.400	1.515
Width (mm)	455	466	685	575	750	630	750
Depth (mm)	600	670	805	736	835	840	920
Wheel diameter (mm)	300	350	800	350	800	400	800
Hose length (m)	5	5	5	5	5	12	12
Discharge time (s)	120	130	130	150	150	170	170
Discharge range (m)	5/6	6/7	6/7	7/8	7/8	8/9	8/9
Temperature range (°C)	-10 to 50	-10 to 50	-10 to 50	-10 to 50	-10 to 50	-10 to 50	-10 to 50
Service pressure (Mpa)	0,8	0,8	0,8	0,8	0,8	0,8	0,8
Tested pressure (Mpa)	4,0	4,0	4,0	4,0	4,0	4,0	4,0
Extinguishing agent IRAM std.#	3515	3515	3515	3515	3515	3515	3515
Fire extinguisher IRAM std.#	3541	3541	3541	3541	3541	3541	3541
Models							
Code	B203	B207	B327	B211	B328	B215	B228

AFFF extinguishing agent is certified under UL 162 standards

Water mist stored pressure fire extinguishers

Portable

- Stainless steel cylinders welded with TIG system (Tungsten Inert Gas).
- 100% Hydrostatically tested.
- Unique surface treatment. Semi matt polished extinguisher.
- Forged brass valve with pressure gauge
- Synthetic dielectric rubber hose of great maneuverability. The nozzle produces a very thin spray that increases the cooling power. It doesn't produce thermic neither electric shock. Testing in concordance to IRAM 3544 standards at a tension of 100kv.
- Ventouri type nozzle.
- Compressed air pressurization.
- Easy to use compact equipment. Simple maintenance.
- Extinguishing agent: Tri-distilled and deionized water. It doesn't affect the ozone layer and neither contributes to global warming.



Tech Specs

Nominal capacity (kg)	10 dm ³
Loaded weight (kg)	13,00
Height (mm)	620/650
Width (mm)	240
Depth (mm)	190
Discharge time (s)	75
Discharge range (m)	3/4
Temperature range (°C)	5 to 50
Service pressure (Mpa)	0,8
Tested pressure (Mpa)	2,0
Fire extinguisher IRAM std.#	3693
Wall bracket	Yes

Model

Code	A147
------	------

HCFC stored pressure fire extinguishers

Portable

- Steel cylinders welded with MIG system (Metal Inert Gas).
- 100% Hydrostatically tested.
- Unique surface treatment, highly resistant to corrosion: mechanical pickled, phosphatized, passivated and painted with polyester powder paint.
- Forged brass valve with pressure gauge.
- Synthetic rubber hose of great maneuverability.
- Pressurized with Argon gas.
- Easy to use compact equipment. Simple maintenance.
- Clean extinguishing agent. Doesn't leave residues after use. Ideal for electronic equipments, data centers, museums, surgery rooms, etc.



Note: Fire extinguishers based on HCFC can be delivered in wheeled version with different capacities. Please consult us.



Tech Specs					
Nominal capacity (kg)	1 kg Ø3	1 kg Ø4	2,5 kg	5 kg	10 kg
Loaded weight (kg)	1,90	1,70	4,60	8,50	16,50
Height (mm)	340	250	415	480	655
Width (mm)	92	110	220	225	230
Depth (mm)	76	101	125	153	182
Discharge time (s)	8	8	10	10	18
Discharge range (m)	3	3	4	5	6
Temperature range (°C)	-20 to 50	-20 to 50	-20 to 50	-20 to 50	-20 to 50
Service pressure (Mpa)	0,8	0,8	0,8	0,8	0,8
Tested pressure (Mpa)	2,0	2,0	2,0	2,0	2,0
Extinguishing agent IRAM std.#	3526-1	3526-1	3526-1	3526-1	3526-1
Fire extinguisher IRAM std.#	3504	3504	3504	3504	3504
Strap bracket	Yes	Yes	Optional	Optional	Optional
Wall bracket	No	No	Yes	Yes	Yes
Models					
Code	A138	A142	A139	A140	A141

HFC 236fa stored pressure fire extinguishers

Portable

- Steel cylinders welded with MIG system (Metal Inert Gas).
- 100% Hydrostatically tested.
- Unique surface treatment, highly resistant to corrosion: mechanical pickled, phosphatized, passivated and painted with polyester powder paint.
- Forged brass valve with pressure gauge.
- Synthetic rubber hose of great maneuverability.
- Nitrogen gas pressurization.
- Easy to use compact equipment. Simple maintenance.
- Clean extinguishing agent. Doesn't leave residues after use. Ideal for electronic equipments, data centers, museums, surgery rooms, etc.



Note: Fire extinguishers based on HFC236fa can be delivered in wheeled version with different capacities. Please consult us.



Tech Specs					
Nominal capacity (kg)	1 kg Ø3	1 kg Ø4	2,5 kg	5 kg	10 kg
Loaded weight (kg)	2,15	1,75	4,60	8,50	16,50
Height (mm)	340	250	415	480	655
Width (mm)	92	110	220	225	230
Depth (mm)	76	101	125	153	182
Discharge time (s)	8	8	10	10	18
Discharge range (m)	3	3	4	5	6
Temperature range (°C)	-20 to 50	-20 to 50	-20 to 50	-20 to 50	-20 to 50
Service pressure (Mpa)	0,8	0,8	0,8	0,8	0,8
Tested pressure (Mpa)	2,0	2,0	2,0	2,0	2,0
Extinguishing agent IRAM std.#	3526-5	3526-5	3526-5	3526-5	3526-5
Fire extinguisher IRAM std.#	3504	3504	3504	3504	3504
Strap bracket	Yes	Yes	Optional	Optional	Optional
Wall bracket	No	No	Yes	Yes	Yes
Models					
Code	A173	A174	A175	A176	A177

Wet chemical (AK) stored pressure fire extinguishers

Portable

- Stainless steel cylinders welded with TIG system (Tungsten Inert Gas). Not magnetic.
- 100% Hydrostatically tested.
- Unique surface treatment. Semi matt polished extinguisher.
- Forged brass valve with pressure gauge.
- Synthetic dielectric rubber hose of great maneuverability.
- The nozzle produces a very thin spray that increases the cooling power and doesn't allow the grease to spread.
- Compressed air pressurization.
- Easy to use compact equipment. Simple maintenance.
- The wet agent is an aqueous solution of potassium acetate, specially designed to be used in commercial kitchens with greases and oils of vegetal and animal origin.



Tech Specs		
Nominal capacity (kg)	6 dm ³	10 dm ³
Loaded weight (kg)	8,25	13,00
Height (mm)	470	620
Width (mm)	270	270
Depth (mm)	190	190
Discharge time (s)	50	75
Discharge range (m)	3/4	3/4
Temperature range (°C)	5 to 50	5 to 50
Service pressure (Mpa)	0,8	0,8
Tested pressure (Mpa)	2,0	2,0
Extinguishing agent IRAM std.#	3697	3697
Fire extinguisher IRAM std.#	3694	3694
Wall bracket	Yes	Yes
Models		
Code	A148	A149

Carbon dioxide stored pressure fire extinguishers

Portable and wheeled

- Steel cylinder without sew
- 100% Hydrostatically tested.
- Surface treatment. Painted with vitric painting.
- Forged brass valve with different auctioning systems (robinet, trigger and lever). Safety device.
- Synthetic dielectric rubber hose with steel mesh. Dielectric nozzle.



Tech Specs											
Nominal capacity (kg)	1kg	2kg	3,5kg	5kg	7kg	10kg	20kg	20kg ^(*)	30kg	40kg ^(*)	60kg ^(*)
Loaded weight (kg)	4	9	14	20	29	35	61	70	100	122	200
Height (mm)	340	520	600	790	1000	1215	940	1330	1315	1060	1435
Width (mm)	89	254	250	310	335	335	472	442	472	710	710
Depth (mm)	89	114	140	140	270	270	410	320	410	490	490
Wheel diameter (mm)	-	-	-	-	-	200	380	300	380	500	500
Hose length (m)	-	-	-	900	900	1800	3000	3000	3000	3000	3000
Discharge time (s)	14	9	9	14	30	50	70	70	120	120	150
Discharge range (m)	1,5/3										
Temperature range (°C)	-20 to 50										
Service pressure (Mpa)	15	15	15	15	15	15	15	15	15	15	15
Tested pressure (Mpa)	25	25	25	25	25	25	25	25	25	25	25
Extinguishing agent IRAM std.#	41170										
Fire extinguisher IRAM std.#	3509	3509	3509	3509	3509	3565	3565	3565	3565	3565	3565
Wall bracket	Yes	Yes	Yes	Yes	Yes	No	No	No	No	No	No
Models											
Code	C301	C302	C303	C304	C305	C306	C307	C308	C309	C310	C311
Extinguishing rating	-	2B-C	3B-C	5B-C	5B-C	-	-	-	-	-	-

D Dry Chemical Powder stored pressure fire extinguishers

Portable

- Steel cylinders welded with MIG system (Metal Inert Gas).
- 100% Hydrostatically tested.
- Unique surface treatment, highly resistant to corrosion: mechanical pickled, phosphatized, passivated and painted with polyester powder paint.
- Forged brass valve with pressure gauge.
- Synthetic rubber hose of great maneuverability.
- Nitrogen gas pressurization.
- Easy to use compact equipment. Simple maintenance.



Tech Specs		
Nominal capacity (kg)	5 kg	10 kg
Loaded weight (kg)	8,50	16,50
Height (mm)	480	655
Width (mm)	225	230
Depth (mm)	153	182
Discharge time (s)	10/13	18/22
Discharge range (m)	5/6	6/7
Temperature range (°C)	-20 to 50	-20 to 50
Service pressure (Mpa)	1,4	1,4
Tested pressure (Mpa)	3,5	3,5
Fire extinguisher IRAM std.#	3523	3523
Wall bracket	Yes	Yes
Models		
Code	A163	A164

Automatic stored pressured fire extinguishers

- Steel cylinders welded with MIG system (Metal Inert Gas).
- 100% Hydrostatically tested.
- Unique surface treatment, highly resistant to corrosion: mechanical pickled, phosphatized, passivated and painted with polyester powder paint.
- Pressure gauge with protection.
- Automatic activation sprinklers (NFPA).
- Compact equipment. Simple maintenance.
- Allows 24 hours of protection. No human intervention is necessary to active and use the equipment.
- Easy to install. No piping required.



Tech Specs		
Nominal capacity (kg)	5kg	10kg
Loaded weight (kg)	11,40	18,10
Height (mm)	340	360
Width (mm)	270	320
Temperature range (°C)	68	68
Service pressure (Mpa)	0,8	0,8
Tested pressure (Mpa)	2,0	2,0
Roof support	Yes	Yes
Models Dry Chemical Powder ABC		
Extinguishing agent IRAM std.#	3569	3569
Code	A171	A172
Models HCFC		
Extinguishing agent IRAM std.#	3526-1	3526-1
Code	A167	A168
Models HCFC		
Extinguishing agent IRAM std.#	3526-5	3526-5
Code	A169	A170

Choosing a extinguisher

To choose the ideal fire extinguisher, first of all it is necessary to know what type or class of fire is needed to be extinguished.

The dotation (quantity) and capacity of the fire extinguishers are determinate by standards and local laws. Consult health and safety professionals.

Classes of fires – Types of extinguisher



Class A fires. Solid fuels. After burning, these kinds of fires leave embers or ashes, like: paper, cloth and wood, etc.



Class B fires. Flammable liquids and gases, such as: gasoline, paint, natural gas, alcohol, butane, etc.



Class C fires: Are fires involving energized electrical equipment such as motors, transformers, and appliances.



Class D fires: Are fires in combustible metals and chemical reactive products, such as: magnesium, titanium, sodium and potassium.



Class K fires: Are fires in kitchens involving oils and greases from vegetal or animal origin.

In the following chart you can see which agent is ideal for each case.

Kind of extinguisher										
Class of fires	Dry Powders			Water			CO ₂	HCFC	HFC 236fa	Wet agent
	ABC	BC	D	Dest	AFFF	Mist				
		++	-	-	+	++	+	-	+	+
		++	++	-	-	++	-	+	+	-
		++	++	-	-	-	++	++	++	-
		-	-	++	-	-	-	-	-	-
		-	-	-	-	-	-	-	-	++
							++	+		
							Very efficient	Efficient		



Our values define us

Quality, reliability and commercial respect

Our fire extinguisher line:

ABC, BC, D Dry Chemical Powders / Water / AFFF /
Water mist / HCFC / HFC 236fa / CO2 / AK

40
YEARS

Fadesa, much more than a fire extinguisher



extintoresfadesa.com.ar